

## AUTOMATIC N.C. GAS SOLENOID VALVE

### GCAO ...

#### APPLICATION

Without power they are closed, when powered they are open. Approved Class A Group 2.

#### Features

- Construction : brass body
- Linkage : screwed female EN 10226
- Protection : IP 65
- Working temperature : - 15...+ 60°C

Code	DN	Power supply		P.max <sup>(1)</sup> mbar	Flow rate m <sup>3</sup> /h <sup>(2)</sup>		Data Sheet
		V	W		0.5 mbar	1 mbar	
<b>GCAO 810</b>	3/8"	230 V AC	9	200	0,92	1,4	G 914
<b>GCAO 410</b>	3/8"	24 V AC	7	200	0,92	1,4	G 914
<b>GCAO 210</b>	3/8"	12 V DC	8,5	200	0,92	1,4	G 914
<b>GCAO 815</b>	1/2"	230 V AC	9	200	0,92	1,4	G 914
<b>GCAO 415</b>	1/2"	24 V AC	7	200	0,92	1,4	G 914
<b>GCAO 215</b>	1/2"	12 V DC	8,5	200	0,92	1,4	G 914
<b>GCAO 820</b>	3/4"	230 V AC	9	200	0,92	1,4	G 914
<b>GCAO 420</b>	3/4"	24 V AC	7	200	0,92	1,4	G 914
<b>GCAO 220</b>	3/4"	12 V DC	8,5	200	0,92	1,4	G 914

(1) – Maximum working pressure.

(2) – Flow of methane with pressure drop of 0.5 mbar (5mmWG) and 1 mbar (10 mmWG).

100 mbar = 10 kPa = 1.000 mm.WG